THICKENER SYSTEM FOR COSMETIC COMPOSITIONS

BACKGROUND OF THE INVENTION

5 Field of the Invention

[0001]

The invention relates to improved thickening systems for cosmetic compositions, particularly those in lotion and cream form.

10

15

The Related Art

[0002]

Aqueous cosmetic compositions often require thickeners to achieve an aesthetically pleasing viscosity. Fluids that flow with a watery consistency too rapidly run off the treated skin areas. For a cosmetic to be effective, it often must have substantivity. Thickeners provide this substantivity. Furthermore, low viscosity formulas which may be skin effective nevertheless through their wateriness signal ineffectiveness to the consumer. Products of watery

20

with expectations of rich and creamy products.

consistency are also aesthetically displeasing to consumers

10

15

20

Zhang et al. J6721(C) 01-0505-CPI

[0003]	U.S. Patent 5,422,112 (Williams) discloses a triple thickener system including xanthan gum, magnesium aluminum silicate and polyacrylamide. The compositions are said to be particularly effective for thickening alpha-hydroxy carboxylic acids and salts thereof, especially at low pH.
[0004]	U.S. Patent 5,874,095 (Deckner et al.) reports an enhanced skin penetration system for improved topical delivery of drugs. Essential to the system is a nonionic polyacrylamide of high molecular weight described as effective at low pH.
[0005]	U.S. Patent 5,952,395 (Lorant) and U.S. Patent 5,891,452 (Sebillote-Arnaud et al.) describe cosmetic compositions gelled into an emulsion with a cross-linked poly(2-acrylamido-2-methylpropanesulfonic acid).
[0006]	Countless numbers of other thickening agents are known in the literature. Perhaps this plethora intimates that not all thickening agents are equally effective for any particular type of formulation.
[0007]	Indeed, there are some formulations which are extremely difficult to thicken, and even if initially thickened may have storage stability problems. Low pH systems are particularly

sensitive and difficult.

10

15

20

Zhang et al. J6721(C) 01-0505-CPI

[8000]	Accordingly, it is an object of the present invention to provide a thickener system and thickened cosmetic compositions of sufficiently aesthetically pleasing viscosity and skinfeel.
[0009]	It is another object of the present invention to provide thickening systems for cosmetic compositions that are effective at low pH.
[00010]	It is still another object of the present invention to provide thickening systems for water and oil emulsion cosmetic compositions that also function as stabilizers preventing phase separation.
[00011]	These and other objects of the present invention will more readily become apparent from the description and examples which follow.
	SUMMARY OF THE INVENTION
[00012]	A cosmetic composition is provided which includes: (i) from about 0.001 to about 5% by weight of a polysaccharide gum;

taurate copolymer; and

(ii) from about 0.001 to about 10% by weight of a

(iii) a cosmetically acceptable carrier, wherein the composition has a pH of less than 7.

DETAILED DESCRIPTION OF THE INVENTION

5 [00013]

Now it has been discovered that taurate copolymers in combination with polysaccharide gums are highly effective thickening agents for low pH cosmetic compositions. This system is particularly useful for building viscosity in relatively acidic compositions, especially those containing C_1 - C_{25} alphaor beta-hydroxycarboxylic acids. Beyond building viscosity, the thickening system of this invention has the further advantage of stabilizing oil and water emulsions and providing a good skinfeel.

10

[00014]

15

20

Accordingly, a first element of compositions according to the present invention is that of a taurate copolymer. A particularly preferred copolymer is one wherein the taurate repeating monomer unit is acryloyl dimethyltaurate (in either free acid or salt form). Monomers forming the copolymer with taurate may include: styrene, acrylic acid, methacrylic acid, vinyl chloride, vinyl acetate, vinyl pyrrolidone, isoprene, vinyl alcohol, vinyl methylether, chloro-styrene, dialkylamino-styrene, maleic acid, acrylamide, methacrylamide and mixtures thereof. Where the term

"acid" appears, the term means not only the free acid but also C_1 - C_{30} alkyl esters, anhydrides and salts thereof. Preferably but not exclusively the salts may be ammonium, alkanolammonium, alkali metal and alkaline earth metal salts.

[00015]

Most preferred as the copolymer is Acryloyl
Dimethyltaurate/Vinyl Pyrrolidone Copolymer, which is the
INCI nomenclature, for a material supplied by Clariant
Corporation under the trademark Aristoflex® AVC, having
the following general formula:

10

5

wherein n and m are integers which may independently vary from 1 to 10,000.

15

Zhang et al. J6721(C) 01-0505-CPI

[00018]

- [00016] Average molecular weight of copolymers according to the invention may range from about 1,000 to about 3,000,000, preferably from about 3,000 to about 100,000, optimally from about 10,000 to about 80,000.
- 5 [00017] Amounts of the taurate copolymer may range from about 0.001 to about 10%, preferably from about 0.01 to about 8%, more preferably from about 0.1 to about 5%, optimally from about 0.2 to about 1% by weight of the composition.
 - A second element of compositions according to the present invention is that of a polysaccharide. Examples include natural or synthetic varieties of starches, gums and cellulosics. Representative of the starches are chemically modified starches such as aluminum starch octenylsuccinate. Suitable gums include xanthan, sclerotium, pectin, karaya, arabic, gelatin, agar, guar, carrageenan, alginate and combinations thereof. Suitable cellulosics include hydroxyethyl cellulose, hydroxypropyl cellulose, hydroxypropyl methylcellulose, methylcellulose, ethylcellulose and sodium carboxy methylcellulose.
- 20 [00019] Amounts of the polysaccharide may range from about 0.001 to about 5%, preferably from about 0.1 to about 2%, optimally from about 0.2 to about 0.5% by weight.

[00020] Advantageously but not necessarily compositions according to the present invention may contain an alpha- or beta-hydroxycarboxylic acid. The former may be a C_1 - C_{25} alpha-hydroxycarboxylic acid of formula I

5

10

.

15

being saturated or unsaturated, isomeric or nonisomeric, straight or branched chain, or in cyclic form having 5 or 6 ring members, and in addition, R and R¹ may carry OH, CHO, COOH and alkoxy groups having 1 to 9 carbon atoms, the a-hydroxyacid existing as a free acid or lactone form, or in salt form with an organic amine base or an inorganic alkali, and as stereoisomers, and D, L, and DL forms when R and R¹ are not identical.

wherein R and R¹ are H, F, Cl, Br, alkyl, aralkyl or aryl groups

[00021]

Illustrative of this group of materials are 2-hydroxyethanoic acid (glycolic acid); 2-hydroxypropanoic acid (lactic acid); 2-methyl 2-hydroxypropanoic acid (methyllactic acid); 2-hydroxybutanoic acid; 2-hydroxypentanoic acid;

10

15

20

25

[00022]

Zhang et al. J6721(C) 01-0505-CPI

2-hydroxyhexanoic acid; 2-hydroxyheptanoic acid; 2-
hydroxyoctanoic acid; 2-hydroxynonanoic acid; 2-
hydroxydecanoic acid; 2-hydroxyundecanoic acid;
2-hydroxydodecanoic acid (a-hydroxylauric acid); 2-
hydroxytetradecanoic acid (a-hydroxymyristic acid); 2-
hydroxyhexadecanoic acid (a-hydroxypalmitic acid);
2-hydroxyoctadecanoic acid (a-hydroxystearic acid); 2-
hydroxyeicosanoic acid (a-hydroxyarachidonic acid); 2-
phenyl 2-hydroxyethanoic acid (mandelic acid);
2,2-diphenyl 2-hydroxyethanoic acid (benzilic acid); 3-phenyl
2-hydroxypropanoic acid (phenyllactic acid); 2-phenyl 2-
methyl 2-hydroxyethanoic acid (atrolactic acid);
2-(4'-hydroxyphenyl) 2-hydroxyethanoic acid; 2-
(4'-chlorophenyl 2-hydroxyethanoic acid; 2-(3'-hydroxy-4'-
methoxyphenyl) 2-hydroxyethanoic acid;
2-(4'-hydroxy-3'-methoxyphenyl) 2-hydroxyethanoic acid; 3-
(2-hydroxyphenyl) 2-hydroxypropanoic acid; 3-(4'-
hydroxyphenyl) 2-hydroxypropanoic acid; and
2-(3',4'-dihydroxyphenyl) 2-hydroxyethanoic acid.
Most preferred of this group of materials are glycolic acid,
lactic acid, gluconolactone and 2-hydroxyoctanoic acids. The
term "acid" is here again intended to refer to not only the
free acid form but also the esters, lactone and salt forms.
The salts may be selected from alkalimetal, ammonium and

10

15

[00023]

[00024]

Zhang et al. J6721(C) 01-0505-CPI

 C_1 - C_{20} alkyl or alkanolammonium counterions. The beta-hydroxycarboxylic acids are best illustrated by salicylic acid and its derivatives. Levels of the hydroxycarboxylic acids may range from about 0.01 to about 20%, preferably from about 0.2 to about 10%, optimally from about 1 to about 5% by weight.

Compositions of the present invention may either be aqueous or anhydrous. Preferably the compositions are aqueous, especially water and oil emulsions of the W/O or O/W variety. Water when present will be in amounts which may range from about 5 to about 90%, preferably from about 35 to about 70%, optimally between about 40 and 60% by weight.

The pH of aqueous compositions of this invention will be less than 7. Advantageously, pH may range from about 1 to about 6, preferably from 2 to 5.5, optimally from 2.5 to 3.8.

Zhang et al. J6721(C) 01-0505-CPI

Besides water, relatively volatile solvents may also be incorporated within compositions of the present invention. Most preferred are monohydric C ₁ -C ₃ alkanols. These include ethyl alcohol, methyl alcohol and isopropyl alcohol. The amount of monohydric alkanol may range from about 5 to about 50%, preferably from about 15 to about 40%, optimally between about 25 to about 35% by weight. [00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms. [00028] Linear volatile silicone materials generally have viscosities		
Most preferred are monohydric C ₁ -C ₃ alkanols. These include ethyl alcohol, methyl alcohol and isopropyl alcohol. The amount of monohydric alkanol may range from about 5 to about 50%, preferably from about 15 to about 40%, optimally between about 25 to about 35% by weight. [00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.	[00025]	Besides water, relatively volatile solvents may also be
ethyl alcohol, methyl alcohol and isopropyl alcohol. The amount of monohydric alkanol may range from about 5 to about 50%, preferably from about 15 to about 40%, optimally between about 25 to about 35% by weight. [00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		incorporated within compositions of the present invention.
amount of monohydric alkanol may range from about 5 to about 50%, preferably from about 15 to about 40%, optimally between about 25 to about 35% by weight. [00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		Most preferred are monohydric C_1 - C_3 alkanols. These include
about 50%, preferably from about 15 to about 40%, optimally between about 25 to about 35% by weight. [00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		ethyl alcohol, methyl alcohol and isopropyl alcohol. The
optimally between about 25 to about 35% by weight. [00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		amount of monohydric alkanol may range from about 5 to
[00026] Emollient materials in the form of mineral oils, silicone oils and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		about 50%, preferably from about 15 to about 40%,
and synthetic esters may be incorporated into compositions of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		optimally between about 25 to about 35% by weight.
of the present invention. Amounts of the emollients may range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.	[00026]	Emollient materials in the form of mineral oils, silicone oils
range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		and synthetic esters may be incorporated into compositions
range anywhere from about 0.1 to about 30%, preferably between about 0.5 and 20% by weight. [00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		of the present invention. Amounts of the emollients may
[00027] Silicone oils may be divided into the volatile and non-volatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		•
variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		
variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.	[00027]	Silicone oils may be divided into the volatile and non-volatile
materials which have a measurable vapor pressure at ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.	[00027]	·
ambient temperature. Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		•
chosen from cyclic or linear polydimethylsiloxanes containing from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		
from about 3 to about 9, preferably from about 4 to about 5, silicon atoms.		
silicon atoms.		
		from about 3 to about 9, preferably from about 4 to about 5,
[00028] Linear volatile silicone materials generally have viscosities		silicon atoms.
	[00028]	Linear volatile silicone materials generally have viscosities
less than about 5 centistokes at 25°C while cyclic materials		less than about 5 centistokes at 25°C while cyclic materials
typically have viscosities of less than about 10 centistokes.		typically have viscosities of less than about 10 centistokes.

10

Zhang et al. J6721(C) 01-0505-CPI

[00029] Nonvolatile silicone oils useful as an emollient material include polyalkyl siloxanes, polyalkylaryl siloxanes and polyether siloxane copolymers. The essentially non-volatile polyalkyl siloxanes useful herein include, for example, polydimethyl siloxanes with viscosities of from about 5 to about 100,000 centistokes at 25°C.

[00030] Among suitable ester emollients are:

- (1) Alkenyl or alkyl esters of fatty acids having 10 to 20 carbon atoms. Examples thereof include isopropyl palmitate, isopropyl isostearate, isononyl isonanonoate, oleyl myristate, oleyl stearate, and oleyl oleate.
- (2) Ether-esters such as fatty acid esters of ethoxylated fatty alcohols.
- (3) Polyhydric alcohol esters. Ethylene glycol mono and di-fatty acid esters, diethylene glycol mono- and di-fatty acid esters, polyethylene glycol (200-6000) mono- and di-fatty acid esters, propylene glycol mono- and di-fatty acid esters, polypropylene glycol 2000 monooleate, polypropylene glycol 2000 monostearate, ethoxylated propylene glycol monostearate, glyceryl

20

10

15

20

[00031]

[00032]

[00033]

Zhang et al. J6721(C) 01-0505-CPI

mono- and di-fatty acid esters, polyglycerol poly-fatty esters, ethoxylated glyceryl monostearate, 1,3-butylene glycol monostearate, 1,3-butylene glycol distearate, polyoxyethylene polyol fatty acid ester, sorbitan fatty acid esters, and polyoxyethylene sorbitan fatty acid esters are satisfactory polyhydric alcohol esters. Wax esters such as beeswax, spermaceti, myristyl (4) myristate, stearyl stearate. (5) Sterols esters, of which soya sterol and cholesterol fatty acid esters are examples thereof. The most preferred esters are dicaprylyl ether and isopropyl isostearate. Fatty acids having from 10 to 30 carbon atoms may also be included in the compositions of this invention. Illustrative of this category are pelargonic, lauric, myristic, palmitic, stearic, isostearic, hydroxystearic, oleic, linoleic, ricinoleic, arachidic, behenic and erucic acids. Humectants of the polyhydric alcohol-type may also be

included in the compositions of this invention. The humectant

10

Zhang et al. J6721(C) 01-0505-CPI

aids in increasing the effectiveness of the emollient, reduces scaling, stimulates removal of built-up scale and improves skin feel. Typical polyhydric alcohols include glycerol (also known as glycerin), polyalkylene glycols and more preferably alkylene polyols and their derivatives, including propylene glycol, dipropylene glycol, polypropylene glycol, polyethylene glycol and derivatives thereof, sorbitol, hydroxypropyl sorbitol, hexylene glycol, 1,3-butylene glycol, 1,2,6-hexanetriol, ethoxylated glycerol, propoxylated glycerol and mixtures thereof. For best results the humectant is preferably glycerin. The amount of humectant may range anywhere from 0.5 to 30%, preferably between 1 and 15% by weight of the composition.

[00034]

15

Collectively the water, solvents, silicones, esters, fatty acids and/or humectants are viewed as cosmetically acceptable carriers for the compositions of the invention. Total amount of carrier will range from about 1 to 99.9%, preferably from about 80 to 99% by weight.

[00035]

20

Cosmetic compositions of the present invention may be in any form. These forms may include lotions, creams, roll-on formulations, mousses, aerosol sprays and cloth- or padapplied formulations.

[00036]

the present invention. Total concentration of the emulsifier will range from about 0.1 to about 40%, preferably from about 1 to about 20%, optimally from about 1 to about 5% by weight of the total composition. The emulsifier may be selected from the group consisting of anionic, nonionic, cationic and amphoteric actives. Particularly preferred nonionic surfactants are those with a C_{10} - C_{20} fatty alcohol or acid hydrophobe condensed with from about 2 to about 100 moles of ethylene oxide or propylene oxide per mole of hydrophobe; C_2 - C_{10} alkyl phenols condensed with from 2 to 20 moles of alkylene oxide; mono- and di- fatty acid esters of ethylene glycol; fatty acid monoglyceride; sorbitan, mono- and di- C_8 - C_{20} fatty acids; and polyoxyethylene sorbitan as well as combinations thereof. Alkyl polyglycosides and

Emulsifiers may also be present in cosmetic compositions of

10

5

15

[00037]

20

Preferred anionic emulsifiers include soap, alkyl ether sulfate and sulfonates, alkyl sulfates and sulfonates, alkylbenzene sulfonates, alkyl and dialkyl sulfosuccinates, C_8 - C_{20} acyl isethionates, C_8 - C_{20} alkyl ether phosphates, alkylethercarboxylates and combinations thereof.

saccharide fatty amides (e.g. methyl gluconamides) are also

suitable nonionic emulsifiers.

[00038]

Sunscreen actives may also be included in compositions of the present invention. Particularly preferred are such materials as Avobenzene, available as Parsol® 1789, ethylhexyl p-methoxycinnamate, available as Parsol® MCX, and benzophenone-3, also known as Oxybenzone. Inorganic sunscreen actives may be employed such as microfine titanium dioxide, polyethylene and various other polymers. Amounts of the sunscreen agents will generally range from about 0.1 to about 30%, preferably from about 2 to about 20%, optimally from about 4 to about 10% by weight.

10

5

[00039]

[0000]

15

20

Preservatives can desirably be incorporated into the cosmetic compositions of this invention to protect against the growth of potentially harmful microorganisms. Suitable traditional preservatives for compositions of this invention are alkyl esters of para-hydroxybenzoic acid. Other preservatives which have more recently come into use include hydantoin derivatives, propionate salts, and a variety of quaternary ammonium compounds. Cosmetic chemists are familiar with appropriate preservatives and routinely choose them to satisfy the preservative challenge test and to provide product stability. Particularly preferred preservatives are iodopropynyl butyl carbamate, phenoxyethanol, methyl paraben, propyl paraben, imidazolidinyl urea, sodium dehydroacetate and benzyl alcohol. The preservatives should

be selected having regard for the use of the composition and possible incompatibilities between the preservatives and other ingredients in the emulsion. Preservatives are preferably employed in amounts ranging from about 0.01% to about 2% by weight of the composition.

[00040]

[00041]

For additional thickening, it is preferred to have magnesium aluminum silicate, commercially available as Veegum®, sold by the R.T. Vanderbilt Company. Amounts of this inorganic thickening agent may range from about 0.01 to about 10%, preferably from about 0.5 to about 1.2% by weight.

10

5

Minor adjunct ingredients may also be present in the cosmetic compositions. Among them may be the water-insoluble vitamins such as Vitamin A Palmitate, Vitamin E Acetate and DL-panthenol. Also useful are: retinol, ceramides and herbal extracts including green tea and chamomile.

15

[00042] Colorants, fragrances and abrasives may also be included in compositions of the present invention. Each of these substances may range from about 0.05 to about 5%, preferably between 0.1 and 3% by weight.

[00044]

5

10

15

[00043]	Except in the operating and comparative examples, or where
	otherwise explicitly indicated, all numbers in this description
	indicating amounts of material ought to be understood as
	modified by the word "about".

The term "comprising" is meant not to be limiting to any subsequently stated elements but rather to encompass non-specified elements of major or minor functional importance. In other words the listed steps, elements or options need not be exhaustive. Whenever the words "including" or "having" are used, these terms are meant to be equivalent to "comprising" as defined above.

[00045] The following Examples will more fully illustrate the embodiments of this invention. All parts, percentages and proportions referred to herein and in the appended claims are by weight unless otherwise indicated.

EXAMPLES 1-8

[00046] Typical formulations according to the present invention are described below.

では表すいい。 1000年 で

Zhang et al. 16721(C) 01-0505-CPI

Ingredients				Example (Example (Weight %)			
	-	2	က	4	5	9	7	8
Disodium EDTA	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
Methyl Paraben	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
Aloe Vera	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Magnesium Aluminum	09.0	09.0	09'0	09'0	09.0	09.0	09.0	09.0
Silicate								
Glycerin	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00
Butylene Glycol	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00
Xanthan Gum	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Cetearyl Alcohol	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50
Sorbitan Stearate	1.10	1.10	1.10	1.10	1.10	1.10	1.10	1.10
PEG-100 Stearate	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
Glyceryl Dilaurate	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
Stearic Acid	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00
Sucrose Polystearate	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
Propvlparaben	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Tocopheryl Acetate	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Ascorbyl Palmitate	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
Octyl Methoxycinnamate	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Dimethicone	1.00	2.00	1.00	0.50	3.00	1.00	5.00	1.00
Dicaprvlvl Ether	4.00	3.00	6.00	00'9	2.00	3.00	0.50	0.50
Isopropy Isostearate	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50
Glycolic Acid (80% Active)	8.00	11.40	8.40	4.60	10.60	12.40	10.80	8.80

Zhang et al. J6721(C) 01-0505-CPI

Ammonium Hydroxide	1.80	2.80	1.80	0.50	2.40	3.00	2.50	1.80
Polymethyl Methacrylate	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
Aluminum Starch	2.00	2.00	3.00	1.50	0.50	3.00	2.50	2.00
Octenylsuccinate								
Acryloyl Dimethyltaurate	1.00	1.30	1.50	2.00	4.00	0.50	0.50	1.00
Copolymer (7% Active)								
Bisabolol	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Retinol	0.02	0.02	0.02	0.02	0.02	0.02	0.05	0.02
Fragrance	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
Water	Balance							

10

Zhang et al. J6721(C) 01-0505-CPI

EXAMPLE 9

[00047] A series of comparative experiments were conducted to

measure the relative thickening effectiveness of various

polysaccharides and synthetic polymers in low pH systems.

Materials utilized in the comparative experiments are

identified below.

Thickener	INCI Name
Keltrol®	Xanthan gum
Natrosol® 250 HHR	Hydroxyethyl cellulose
Solanace®	Potato Starch Modified
Sepigel® 305	Polyacrylamide/C13-14 Isoparaffin/Laureth-7
Carbopol® 934	Crosslinked Polyacrylate
Aristoflex® AVC	Acryloyl Taurate/Vinyl Pyrrolidone Copolymer

[00048] All viscosity measurements were conducted using a Brookfield RVT instrument, Spindle No. 4 at 20 rpm and 23°C.

10

Zhang et al. J6721(C) 01-0505-CPI

[00049] Table 1 reports the effect of three polysaccharide thickeners.

Keltrol® is representative of natural gums. Natrosol® 250 HHR is representative of chemically modified cellulosic gums.

Solanace® is representative of modified starches. Each

thickener was formulated at 1% in water to form a gel.

Second and third columns report results on gels further

including 8% glycolic acid (AHA) and 8% glycolic

acid/ammonium glycolate (AHA-Ammonium), respectively.

In the latter system, the acid to salt molar ratio was 3.4:1 to

simulate electrolyte effects. None of the polysaccharide

thickeners by themselves achieve viscosities much beyond

5,000 cps, at low pH.

TABLE 1
Polysaccharide Thickener

	1% G	iel	1% G	el +	1% Gel + 8	% AHA-
			8% A	.HA	Ammo	nia
Thickener	Viscosity (cps)	рН	Viscosity (cps)	рН	Viscosity (cps)	рН
Keltrol®	1,600 5.50		5,170	2.00	3,540	3.62
Natrosol®	2,580	6.80	2,290	1.90	2,130	3.63
Solanace®	327	8.20	<100	1.90	<100	3.62

Zhang et al. J6721(C) 01-0505-CPI

[00050]

Table 2 reports the effect on thickening of three synthetic polymers, including Aristoflex® AVC representative of taurate polymers of the present invention. Table 3 reports on gel compositions identical to those tested in Table 2 except the synthetic polymers have been increased to the 2% level.

TABLE 2
Polymer Thickener

	1% G	el	1% Ge 8% A		1% Gel + 8% AHA- Ammonia	
Thickener	Viscosity (cps)	рН	Viscosity (cps)	рН	Viscosity (cps)	рН
Sepigel® 305	5,400 6.30		<1,000	1.84	<100	3.61
Carbopol® 934	152	2.90	<100	1.84	<100	3.60
Aristoflex® AVC	48,000	4.82	1,380	1.96	<100	3.64

TABLE 3
Polymer Thickener

	2% G	el	2% Ge 8% A		2% Gel + 8 Ammo	
Thickener	Viscosity (cps)	рН	Viscosity (cps)	рН	Viscosity (cps)	рН
Sepigel® 305	19,995	6.00	<1000	2.00	<100	3.6
Carbopol® 934	1,735	2.80	<100	1.90	<100	3.5
Aristoflex® AVC	40,000	4.80	20,500	2.00	2,555	3.6

[00051]

Table 4 lists the viscosity effect of combining 1% each of the polysaccharide thickeners with Sepigel® 305. Table 5 reports the combination of the polysaccharides each with Carbopol® 934. Finally, Table 6 reports results according to the present invention wherein the polysaccharides are matched with Aristoflex® AVC.

TABLE 4
Sepigel® + Polysaccharide

	1% +	1%	1% + 3	1% +	1% + 1	1% + 1% +	
			8% <i>F</i>	\HA	8% AHA-A	mmonia	
Thickener	Viscosity (cps)	рН	Viscosity (cps)	рН	Viscosity (cps)	рН	
Sepigel® + Keltrol®	3,740	5.30	10,000	2.00	6,110	3.61	
Sepigel® + Natrosol®	31,050	6.50	10,380	1.86	3,980	3.60	
Sepigel® + Solanace®	13,150	8.14	195	1.89	250	3.61	

TABLE 5

5

${\sf Carbopol} \, {\mathbb R} \, + \, {\sf Polysaccharide}$

	1% + 1%		1% + 1% + 8% AHA		1% + 1% + 8% AHA-Ammonia	
Thickener	Viscosity	рН	Viscosity	рΗ	Viscosity	PH
	(cps)		(cps)		(cps)	
Carbopol® + Keltrol®	5,420	3.43	7,350	1.97	5,950	3.58
Carbopol® + Natrosol®	350	2.98	240	1.85	4,050	3.57
Carbopol® + Solanace	20,700	3.28	210	1.88	200	3.58

TABLE 6
Aristoflex® + Polysaccharide

	1% + 1%		1% + 1% +		1% + 1% +	
			8% AHA		8% AHA-Ammonia	
Thickener	Viscosity	рН	Viscosity	pН	Viscosity	pН
	(cps)		(cps)		(cps)	
Aristoflex® +	10,500	5.16	18,700	2.06	10,940	3.65
Xanthan Gum						
Aristoflex® +	61,000	5.79	24,400	1.94	10,380	3.60
Natrosol®						
250 HHR						
Aristoflex® +	36,200	7.17	3,490	1.95	2,610	3.60
Solanace®						

5 [00052] Based on the results of the combinations reported in Table 4-

6, it is evident that the taurate polymer (Aristoflex® AVC)

under all low pH conditions, especially in the presence of

electrolytes, provides higher viscosity gels with

polysaccharides than do other common synthetic polymeric

thickeners.

[00053] The foregoing description and examples illustrate selected

embodiments of the present invention. In light thereof

variations and modifications will be suggested to one skilled

in the art, all of which are within the spirit and purview of this

invention.

15